



L40U LED post top (L40U)

L40U Post Top LED 32 LED, Type IV, 700mA, Clear Globe 4000K

L40U Post Top LED 32 LED, Type IV, 700mA, Clear Globe 4000K - 77 lm/W

The L40U luminaires feature a one-piece square tapered cast aluminum housing, with a sealed optical system. The cast-aluminum hood includes a photoelectrical hiding decorative finial, assembled on the housing using two built-in hood hinges. <b-Lumec3Dv2/home/index_en.php" target="_blank"><b-Lumec3Dv2/home/index_en.php" target="_blank"><b-Lumec3Dv2/home/index_en.php" target="_blank"><b-Lumec3Dv2/home/index_en.php" target="_blank"><b-Lumec3Dv2/home/index_en.php" target="_blank"><b-Lumec3Dv2/home/index_en.php" target="_blank"><b-Lumec3Dv2/home/index_en.php" target="_blank"><b-Lumec3Dv2/home/index_en.php</td>

Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	70
Photometric Distribution Type Type IV	
Mounting	Pole Top Pole Top
Operating and Electrica	al
Luminaire Input Watts	73
Voltages	120/208/240/277 V
Mechanical and Housin	g
Shape	Square
Initial Performance (IEC Compliant)	
Luminaire Lumens	5648

Efficacy	77 lm/W
Product Data	
Order product name	L40U Post Top LED 32 LED, Type IV, 700mA, Clear Globe
	4000K
Commercial Code	L40U-72W32LED4K-G2-C-LE4
Order code	L40U-72W32LED4K-G2-C-LE4
Catalog Number Description	L40U Post Top LED 32 LED, Type IV, 700mA, Clear Globe
	4000K
Service / Spec Smart	-
Material Nr. (12NC)	LUM70012261

Datasheet, 2018, May 15 data subject to change

L40U LED post top (L40U)

